

Technical Data Sheet

CP-1200-32



PRODUCT DESCRIPTION

CP-1200-32 is a custom-formulated silicon based synthetic fluid providing:

- Extremely long life
- Improved lubrication at high and low temperatures
- Reduced volatility
- Good corrosion protection
- Outstanding oxidation stability

This high-performance lubricant is recommended for use in flooded rotary screw compressors and vacuum pumps, too.

TYPICAL PROPERTIES*

Viscosity @ 40°C , cSt	39.2
Viscosity @ 100°C , cSt	14.0
Viscosity @ 100°F, SUS	193.3
Viscosity @ 210°F, SUS	74.8
Viscosity Index, ASTM D2270	373
Specific Gravity, ASTM D4052	0.96
Density, lb/gal, 60°F, ASTM D4052	8.04
Pour Point °F (°C), ASTM D97	-94 (-70)
Flash Point, C.O.C., °F (°C), ASTM D92	605 (318)

*These values are not intended for use in preparing specifications.

Date revised: 8/08

Vuoto Service srl

Via Filippo Meda, 16 - 20037 Paderno Dugnano (MI) - Italia
Tel. 02.99044533 r.a. - Fax 02.9105503
www.vuotoservice.net - E-mail:info@vuotoservice.net

