

FC VACUUM FILTERS



Vuoto Service Srl
Via Filippo Meda, 16
20037 Paderno Dugnano (MI)

Zona Industriale
67062 Magliano de' Marsi (AQ)

Tel. (0039) 02.99044533
Fax (0039) 02.9105503

These filters are normally installed on the pump's suction in order to protect the pump from dust and other solids that may damage it. They are made with a metal painted casing with a closing cover that is easy to dismantle and reassemble thanks to its clamping clips. Internally, there is a standard filtering paper cartridge of 5-7 micron, but, on demand, it is possible to have filters with polypropylene, stainless steel, and, also for some models, activated carbon cartridges.

CODE	FLOW RATE mc/h	CONNECTION R	DIMENSIONS IN mm			SPARE
			A	B	C	CARTRIDGE
FC700001	24	3/8"	74	64	11	FA600048
FC700002	42	3/4"	102	77	13	FA600052
FC700003	42	1/2"	102	77	13	FA600052
FC700004	108	1-1/4"	172	143	26	FA600003
FC700005	96	1-1/4"	135	81	7	FA600004
FC700006	85	1"	130	80	23	FA600004
FC700007	192	1-1/2"	173	170	18	FA600064
FC700008	310	2"	200	227	15	FA600002
FC700009	360	2-1/2"	200	227	15	FA600002
FC700010	550	3"	276	175	60	FA600030
FC700011	720	4"	276	175	60	FA600030
FC700012	660	3"	291	420	30	FA600026
FC700013	1200	4"	360	590	50	FA600042