

FCM FILTERS WITH THREADED CONNECTION

Vuoto Service Srl

Via Filippo Meda, 16
20037 Paderno Dugnano (MI)

Zona Industriale
67062 Magliano de' Marsi (AQ)

Tel. (0039) 02.99044533

Fax (0039) 02.9105503



These filters are normally installed on side channel blowers and compressors' suction in order to protect the blowers and compressors from dust and other solids that may damage them. They are made with a metal painted casing with a closing cover, that is easy to dismantle and reassemble manually, thanks to the slotted screw at the top. Internally, there is a standard filtering paper of 5-7 micron, but, on demand, it is possible to have filtering elements in other materials, such as polypropylene and stainless steel.

CODE	FLOW RATE mc/h	CONNECTION A	DIMENSIONS IN mm			SPARE CARTRIDGE
			B	C	D	
FCM70002	12	3/8" G	55	43	14	
FCM70003	24	1/2" G	95	75	30	FA600129
FCM70005	36	3/4" G	95	75	30	FA600129
FCM70006	84	1" G	130	85	40	FA600004
FCM70007	96	1-1/4" G	135	85	45	FA600004
FCM70008	200	1-1/2" G	135	116	45	FA600023
FCM70009	270	2" G	170	140	50	FA600130
FCM70010	480	2-1/2" G	210	140	60	FA600091
FCM70011	900	3"	290	175	60	FA600030
FCM70012	1350	4"	320	220	60	FA600131